



**PEDESTRIAN CROSSWALK
DETAIL**

NOTES:

1. Stop Bar shall span across the approach lane and shall installed parallel to the intersecting roadway.
2. Special conditions may warrant exceptions to this detail. The stop bar shall not be placed less than 4 ft. or greater than 30' from the nearest edge of the intersecting roadway.
3. The placement of the stop bar shall be placed so that vehicles have the optimum sight distance along intersecting roadways.
4. The stop sign shall not be blocked by other signs or vegetation and shall be positioned so to face approaching vehicular traffic.
5. The stop bar shall be installed a minimum of 4' offset from a pedestrian crosswalk if one exists.



TOWN OF NAGS HEAD
DEPARTMENT OF ADMINISTRATION
P.O. BOX 99
NAGS HEAD, NC 27959
252.441.7016 • www.nagsheadnc.gov

**TYPICAL STREET STOP SIGN AND
AND STOP BAR PLACEMENT**

* WIDTH FOR COLLECTOR AND LOCAL ACCESS STREETS
** WIDTH FOR SUBCOLLECTOR AND ENVIRONMENTAL STREETS

SCALE: NONE
ISSUE DATE: 8-13-2015
REVISION DATE: 1-3-2019
SHEET NO: 1 OF 1
DRAWN BY: DMR

DETAIL NO.:
300