



## **Town of Nags Head**

Post Office Box 99  
Nags Head, North Carolina 27959  
Telephone (252) 441-5508  
Fax (252) 441-0776  
[www.nagsheadnc.gov](http://www.nagsheadnc.gov)

### **BID FORM**

**FY 24-25 Capital Improvement Project**

**Street Resurfacing**

**Water Main Improvements**

**Drainage Improvements**

**ARTICLE 1 – BID RECIPIENT**

1.01 This Bid is submitted to:

**TOWN OF NAGS HEAD  
c/o ANDY GARMAN, TOWN MANAGER  
5401 S. CROATAN HWY.  
NAGS HEAD, NORTH CAROLINA**

1.02 The undersigned Bidder proposes and agrees, if this Bid is accepted, to enter into an Agreement with Owner in the form included in the Bidding Documents to perform all Work as specified or indicated in the Bidding Documents for the prices and within the times indicated in this Bid and in accordance with the other terms and conditions of the Bidding Documents.

**ARTICLE 2 – BIDDER’S ACKNOWLEDGEMENTS**

2.01 Bidder accepts all of the terms and conditions of the Instructions to Bidders, including without limitation those dealing with the disposition of Bid security. This Bid will remain subject to acceptance for **60** days after the Bid opening, or for such longer period of time that Bidder may agree to in writing upon request of Owner.

**ARTICLE 3 – BIDDER’S REPRESENTATIONS**

3.01 In submitting this Bid, Bidder represents that:

A. Bidder has examined and carefully studied the Bidding Documents, and any data and reference items identified in the Bidding Documents, and hereby acknowledges receipt of the following Addenda:

<u>Addendum No.</u>	<u>Addendum, Date</u>
_____	_____
_____	_____
_____	_____
_____	_____

B. Bidder has visited the Site, conducted a thorough, alert visual examination of the Site and adjacent areas, and become familiar with and satisfied itself as to the general, local, and Site conditions that may affect cost, progress, and performance of the Work.

C. Bidder is familiar with and has satisfied itself as to all Laws and Regulations that may affect cost, progress, and performance of the Work.

D. Bidder has carefully studied all: (1) reports of explorations and tests of subsurface conditions at or adjacent to the Site and all drawings of physical conditions relating to existing surface or subsurface structures at the Site that have been identified in the Supplementary Conditions, especially with respect to Technical Data in such reports and drawings, and (2) reports and drawings relating to Hazardous Environmental Conditions, if any, at or adjacent to the Site that have been identified in the Supplementary Conditions, especially with respect to Technical Data in such reports and drawings.

- E. Bidder has considered the information known to Bidder itself; information commonly known to contractors doing business in the locality of the Site; information and observations obtained from visits to the Site; the Bidding Documents; and any Site-related reports and drawings identified in the Bidding Documents, with respect to the effect of such information, observations, and documents on (1) the cost, progress, and performance of the Work; (2) the means, methods, techniques, sequences, and procedures of construction to be employed by Bidder; and (3) Bidder's safety precautions and programs.
- F. Bidder agrees, based on the information and observations referred to in the preceding paragraph, that no further examinations, investigations, explorations, tests, studies, or data are necessary for the determination of this Bid for performance of the Work at the price bid and within the times required, and in accordance with the other terms and conditions of the Bidding Documents.
- G. Bidder is aware of the general nature of work to be performed by Owner and others at the Site that relates to the Work as indicated in the Bidding Documents.
- H. Bidder has given Engineer written notice of all conflicts, errors, ambiguities, or discrepancies that Bidder has discovered in the Bidding Documents, and confirms that the written resolution thereof by Engineer is acceptable to Bidder.
- I. The Bidding Documents are generally sufficient to indicate and convey understanding of all terms and conditions for the performance and furnishing of the Work.
- J. The submission of this Bid constitutes an incontrovertible representation by Bidder that Bidder has complied with every requirement of this Article, and that without exception the Bid and all prices in the Bid are premised upon performing and furnishing the Work required by the Bidding Documents.

#### **ARTICLE 4 – BIDDER'S CERTIFICATION**

4.01 Bidder certifies that:

- A. This Bid is genuine and not made in the interest of or on behalf of any undisclosed individual or entity and is not submitted in conformity with any collusive agreement or rules of any group, association, organization, or corporation;
- B. Bidder has not directly or indirectly induced or solicited any other Bidder to submit a false or sham Bid;
- C. Bidder has not solicited or induced any individual or entity to refrain from bidding; and
- D. Bidder has not engaged in corrupt, fraudulent, collusive, or coercive practices in competing for the Contract. For the purposes of this Paragraph 4.01.D:
  - 1. "corrupt practice" means the offering, giving, receiving, or soliciting of any thing of value likely to influence the action of a public official in the bidding process;
  - 2. "fraudulent practice" means an intentional misrepresentation of facts made (a) to influence the bidding process to the detriment of Owner, (b) to establish bid prices at artificial non-competitive levels, or (c) to deprive Owner of the benefits of free and open competition;

3. "collusive practice" means a scheme or arrangement between two or more Bidders, with or without the knowledge of Owner, a purpose of which is to establish bid prices at artificial, non-competitive levels; and
4. "coercive practice" means harming or threatening to harm, directly or indirectly, persons or their property to influence their participation in the bidding process or affect the execution of the Contract.

#### **ARTICLE 5 – BASIS OF BID**

- 5.01 This project shall be bid, contracted, and paid on a Lump Sum Basis for each project, except as otherwise provided below. The Bid Tabulation Form provided as part of these Contract Documents provides for the following;
- A. A space for the bidder to indicate his Lump Sum Price for the Base Bid in numeric and written form, which shall comprise all the work except for any item(s) which may be expressly listed as an Additive Alternate or Deductive Alternate thereon.
  - B. Space for the bidder to indicate his separate Lump Sum Price for any Additive Alternate(s), which shall be full compensation for the described item(s) of work which the Owner, at his sole discretion, may elect to ADD TO the Base Bid work.
  - C. Space for the bidder to indicate his separate Lump Sum Price for any Deductive Alternate(s), which shall be full value for the described item(s) of work which the Owner, at his sole discretion, may elect to DEDUCT FROM the Base Bid work.
  - D. Space for the bidder to indicate a separate Unit Price for any item(s) of work for which the precise quantity of same cannot be accurately determined in advance, and which the Owner desires to measure and pay for on a unit price basis. A change order shall be initiated, based on the estimated quantities of such work, and a purchase order issued, before any such work is begun. Unit price information shall be utilized to divide portions of the work that will be applied to grant funds received for the project. Note: Bidders shall not consider this as a comprehensive Unit Price item listing and should rely on the plans and specifications to determine quantities in the calculation of the Lump Sum Price.
  - E. Only those spaces provided for entry of the Base Bid, Additive and/or Deductive Alternates (if any), and the Schedule of Values are to be filled in. Bidders may not add in conditions, provisions, or items of their own; doing so will result in disqualification of the bidder.
- 5.02 Owner reserves the right to reject any or all Bids, including without limitation the rights to reject any or all nonconforming, nonresponsive, unbalanced, or conditional Bids, and to reject the Bid of any Bidder if Owner believes that it would not be in the best interest of Owner to make an award to that Bidder. For comparison purposes alternates will be accepted, following the order of priority established in the Bid Form, until doing so would cause the budget to be exceeded. After determination of the Successful Bidder based on this comparative process and on the responsiveness, responsibility, and other factors, the award may be made to said Successful Bidder on its Base Bid and any combination of its additive alternate Bids for which Owner determines funds will be available at the time of award and in the interest of the Town of Nags Head.

A. The lump sum Base Bid scope of work shall consist of all the necessary labor, materials and equipment necessary for the construction of the following:

1. **Street Resurfacing**

- a. General Base Bid Items: Includes mobilization, bonds, traffic control measures, select fill, milling of street transitions, and pavement patches associated with water line and drainage work.
- b. **S. Memorial Ave:** consists of paving of approximately 140,700 square feet of asphalt surface overlay including S. Memorial Ave. between intersection with Bittern Street and intersection of E. 8<sup>th</sup> St. Paving thickness will be 1.75", a minimum 12' wide asphalt milling for street intersection pavement transitions.
- c. **E. Ario St:** consists of paving of approximately 7,692 square feet of asphalt surface overlay along Atlas St. spanning from Wrightsville Ave to S. Memorial Ave. Paving thickness will be 1" thickness, and a minimum 12' wide asphalt milling for street intersection pavement transitions.
- d. **E. Albatross St.:** consists of paving of approximately 23,365 square feet of asphalt surface overlay along E. Albatross St. spanning from Wrightsville Ave to S. Virginia Dare Trail and includes E. Albatross Beach Access. Paving thickness will be 1.75" thickness through S. Memorial Ave for approximately 14,195 square feet, and 1" from S. Memorial Ave to end of beach access for approximately 9,170 square feet, and a minimum 12' wide asphalt milling for street intersection pavement transitions.
- e. **E. Atlas St.:** consists of paving of approximately 7,528 square feet of asphalt surface overlay along Atlas St. spanning from Wrightsville Ave to S. Memorial Ave. Paving thickness will be 1.75" thickness, and a minimum 12' wide asphalt milling for street intersection pavement transitions.
- f. **E. Driftwood St:** consists of paving of approximately 19,920 square feet of asphalt surface overlay along Driftwood St from S. Croatan Hwy. to S. Virginia Dare Trail. Paving thickness will be 1.75" thickness, and a minimum 12' wide asphalt milling for street intersection pavement transitions.
- g. **E. Abalone St.:** consists of paving of approximately 22,721 square feet of asphalt surface overlay including E Abalone St. between Wrightsville Ave. and S Virginia Dare Trail and includes the E. Abalone St. beach access. Paving thickness will be 1.75", and a minimum 12' wide asphalt milling for street intersection pavement transitions.
- h. **S. Gannett Ave.:** consists of paving of approximately 5,200 square feet of asphalt surface overlay along S. Gannett Ave. spanning from the intersection of S. Gannett Ave and W. 8<sup>th</sup> St. to the southern terminus of S. Gannett Ave. Paving thickness will be 1.75" thickness, and a minimum 12' wide asphalt milling for street intersection pavement transitions.
- i. A supplemental table is provided for alternate bid items which may be added to the scope of work if funds are available. Alternate items are separate and apart from the lump sum price to be provided.

## 2. Water Main Improvements

- a. General Base Bid Items: Includes mobilization, bonds, traffic control measures and select fill.
- b. **S. Memorial Ave. 6-inch water main:** consists of approximately 879 linear feet of water main construction along the west side of South Memorial Avenue from north of the intersection of S. Memorial Avenue and Ario Street and continuing to south of the intersection of South Memorial Ave. and Atlas St., Nags Head, North Carolina. Construction consists of installation of a 6-inch C900 PVC water main with DIP street crossings to be connected to existing water main near the intersection with S. Memorial Ave. and Atlas St. with all appurtenances including but not limited to: valves, fire hydrants, hydrant relocations, tapping sleeves, bends, tees, crosses, elbows, service connections, fittings, supports and restraints. Water main shall achieve separations and setbacks as required by local and state minimum design criteria and as indicated on the plans. Approximately 1,435 square feet of permanent pavement patch will accompany this work.
- c. **Ario St. 6-inch water main:** consists of approximately 392 linear feet of water main construction along the north side of Ario Street beginning north of the intersection of S. Wrightsville Ave. and Ario St. and continuing to north of the intersection of Ario St. and S. Memorial Ave., Nags Head, North Carolina. Construction consists of installation of a 6-inch C900 PVC water main with DIP street crossings to be connected to the new water main along S. Memorial Ave. with all appurtenances including but not limited to: valves, fire hydrants, hydrant relocations, tapping sleeves, bends, tees, crosses, elbows, service connections, fittings, supports and restraints. Water main shall achieve separations and setbacks as required by local and state minimum design criteria and as indicated on the plans. Approximately 535 square feet of permanent pavement patch will accompany this work.
- d. **Albatross St. 6-inch water main:** consists of approximately 767 linear feet water main construction along the north side of Albatross St. beginning north of the intersection of Albatross St. and S. Wrightsville Ave. and continuing east to the north side of the intersection of Albatross St. and S. Virginia Dare Trail. Construction consists of installation of a 6-inch C900 PVC water main with DIP street crossings to be connected to existing water main near the intersection of Albatross St. and S. Virginia Dare Trail with all appurtenances including but not limited to: valves, fire hydrants, hydrant relocations, tapping sleeves, bends, tees, crosses, elbows, service connections, fittings, supports and restraints. Water main shall achieve separations and setbacks as required by local and state minimum design criteria and as indicated on the plans. Approximately 740 square feet of permanent pavement patch will accompany this work.
- e. **Atlas Street 6-inch water main:** consists of approximately 344 linear feet of water main construction along the south side of Atlas Street beginning south of the intersection Atlas Street and South Wrightsville Avenue and continuing east to the intersection of Atlas Street and South Memorial Avenue. Construction consists of installation of a 6-inch C900 PVC water main with DIP street crossings to be connected to the new water main near the intersection of Atlas Street and South Memorial Avenue with all appurtenances including but not limited to: valves, fire

hydrants, hydrant relocations, tapping sleeves, bends, tees, crosses, elbows, service connections, fittings, supports and restraints. Water main shall achieve separations and setbacks as required by local and state minimum design criteria and as indicated on the plans.

### 3. Drainage Improvements

- a. **S. Memorial Ave. at Albatross St.:** consists of drainage infrastructure removal and replacement at the intersection of S. Memorial Ave. and Albatross St. including approximately 56 linear feet of new 30" HPPP pipe. The scope of work consists of one new drop inlet (NCDOT 840.14) with frame and grate (NCDOT 840.16) and (2) pipe connections. Includes removing/demolition of existing 18" RCP, 24" RECP and CMP storms pipe and replacing with new infrastructure as described. Approximately 200 square feet permanent pavement patch will accompany this work. New infrastructure includes all appurtenances and fittings to achieve watertight connections, and all compacted pipe bedding and backfill with clean backfill material for stable pipe installation.
- b. **S. Memorial Ave. at Atlas St.:** consists of drainage infrastructure removal and replacement at the intersection of S. Memorial Ave. and Atlas Street including approximately 46 linear feet of new 18" HPPP pipe. The scope of work consists of one new drop inlet (NCDOT 840.14) with frame and grate (NCDOT 840.16) with one pipe connection. Includes removal/demolition of existing 15" CMP and replacing with new infrastructure as described. Approximately 265 square feet of permanent pavement patch will accompany this work. New infrastructure includes all appurtenances and fittings to achieve watertight connections, and all compacted pipe bedding and backfill with clean backfill material for stable pipe installation.
- c. **S. Memorial Ave. at Driftwood St.:** consists of drainage infrastructure removal and replacement at the intersection of S. Memorial Ave. and Driftwood St including approximately 70 linear feet of new 18" HPPP with drop inlets (NCDOT 840.14) with frame and grate (NCDOT 840.16), and approximately 104 linear feet of new 30" HPPP with drop inlets and 5' stub out, includes a total of (5) new drop inlets with (8) connections. Includes removal/demolition of existing 15" CMP and 24" CMP and replacing with new infrastructure, and connecting to existing piping, as described. Approximately 800 square feet of permanent pavement patch will accompany this work. New infrastructure includes all appurtenances and fittings to achieve watertight connections, and all compacted pipe bedding and backfill with clean backfill material for stable pipe installation.
- d. **S. Memorial Ave. at E. Gallery Row: St.:** consists of drainage infrastructure removal and replacement at the intersection of S. Memorial Ave at E. Gallery Row including approximately 147 linear feet of new 30" HPPP pipe, and approximately 38 linear feet of 18" HPPP, with drop inlets (NCDOT 840.14) with frame and grate (840.16) and one Storm Manhole (NCDO T840.31) with frame and grate (NCDOT 840.54) Includes a total of (4) drop inlets, with 7 connections, and 1 Storm Manhole Junction Box, with 2 connections. Includes removal/demolition of existing 18" CMP. Approximately 860 square feet of pavement patch will accompany this work. New infrastructure includes all appurtenances and fittings to achieve watertight connections, and all compacted pipe bedding and backfill with clean backfill material for stable pipe.

- e. **S. Memorial Ave. at Abalone St.:** consists of drainage infrastructure removal and replacement at the intersection of S. Memorial Ave at Abalone St. including approximately 49 linear feet of new 24" HPPP pipe with drop inlet (NCDOT 840.14) with frame and grate (NCDOT 840.16) and a flared end section. Includes removal/demolition of existing 18" CMP. Approximately 250 square feet of permanent pavement patch will accompany this work. New infrastructure includes all appurtenances and fittings to achieve watertight connections, and all compacted pipe bedding and backfill with clean backfill material for stable pipe installation.
- f. **S. Wrightsville Ave. at Albatross St.:** consists of drainage infrastructure installation including approximately 67 linear feet of new 15" HPPP cross culvert under Albatross Street to be connected to existing infrastructure including 2 new drop inlets (NCDOT 840.14) with frame and grate (840.16). each with one connection. Approximately 220 square feet of permanent pavement patch will accompany this work. New infrastructure includes all appurtenances and fittings to achieve watertight connections, and all compacted pipe bedding and backfill with clean backfill material for stable pipe installation. Also includes construction of approximately 263 linear feet of new drainage swales, approximately 1' deep with 4:1 side slopes.
- g. **S. Memorial Ave. at E. Bonnett St.:** consists of drainage infrastructure removal and replacement at the intersection of S. Memorial Ave at E. Bonnett St including approximately 64 linear feet of new 24" HPPP pipe and approximately 130 linear feet of new 24" HPPP continuing south along S. Memorial Ave. New pipe to connect to existing drop inlets/junction box as shown on the plans. Includes removal/demolition of existing 24" CMP. Approximately 264 square feet of permanent pavement repair will accompany this work. New infrastructure includes all appurtenances and fittings to achieve watertight connections.
- h. **S. Memorial Ave. at Bittern St.:** consists of drainage infrastructure removal and replacement at the intersection of S. Memorial Ave at Bittern St. including approximately 124 linear feet of new 30" HPPP pipe with drop inlets (NCDOT 840.14) with grate and frame (NCDOT 840.16) and a flared end section, and approximately 96 linear feet of new 18" HPPP with drop inlets with frame and grate for a total of (4) new drop inlets with (8) total connections. Includes removal/demolition of existing 15 and 18" CMP. Approximately 1,175 square feet of permanent pavement repair will accompany this work. New infrastructure includes all appurtenances and fittings to achieve watertight connections, and all compacted pipe bedding and backfill with clean backfill material for stable pipe installation.
- i. **ADD ALTERNATE: E. Gallery Row Resurfacing and Drainage Improvements:** consists of paving of approximately 13,962 square feet of asphalt surface overlay along S. Gallery Row spanning from the intersection of Gallery Row and S. Wrightsville Ave. to the intersection of S. Gallery Row and S. Virginia Dare Trail. Paving thickness will be 1.75" thickness, and a minimum 12' wide asphalt milling for street intersection pavement transitions.

Additionally, this **add alternate** consists of installation of approximately 468 linear feet of new 30" dia. HPPP, 33 linear feet of new 18" dia. HPPP and 45 linear feet of 22"x36" corrugated aluminum arch pipe to replace an existing cross street pipe along S Wrightsville Ave. The scope of work will include the addition of one new

concrete junction box (NCDOT 840.31) with manhole frame & cover with (3) pipe connections and the replacement of an existing junction box with a new concrete junction box (NCDOT 840.31) with NCDOT 840.54 frame and grate and (4) connecting pipe connections. Approximately 400 square feet of permanent pavement patch will accompany this work. The alignment is proposed along the southern right-of-way margin of Gallery Row between S. Memorial Ave and S Wrightsville Ave and S. Wrightsville Ave. from the Gallery Row intersection to approximately 2407 S. Wrightsville Ave. New and replacement infrastructure shall include all appurtenances and fittings to achieve watertight connection, and all compacted pipe bedding and clean backfill material for a stable pipe installation.

- j. **ADD ALTERNATE: S. Memorial Ave. South of Bonnet St.** consists of drainage infrastructure installation along S. Memorial Ave. south of Bonnett St. including approximately 130 linear feet of new 24" HPPP. New infrastructure includes all appurtenances and fittings to achieve watertight connections, and all compacted pipe bedding and backfill with clean backfill material for stable pipe installation.
- k. A supplemental table is provided for alternate bid items which may be added to the scope of work if funds are available. Alternate items are separate and apart from the lump sum price to be provided.

<b>General Base Bid Items (see paragraph 5.01.D, page 3)</b>					
<b>Item No.</b>	<b>Description</b>	<b>Est. Quantity</b>	<b>Unit</b>	<b>Unit Price</b>	<b>Total Price</b>
1	Mobilization	1	LS		
2	Traffic Control Measures in accordance with NCDOT requirements	1	LS		
3	Select Fill (estimated)	60	CY		
<b>Subtotal Price</b>					

<b>Street Resurfacing Base Bid</b>					
<b>Item No.</b>	<b>Description</b>	<b>Est. Quantity</b>	<b>Unit</b>	<b>Unit Price</b>	<b>Total Price</b>
1	Roadway clipping and removal	1	LS		
2	Erosion Control Implementation & Removal	1	LS		
3	1.75-inch Surface Overlay (9.5B Asphalt)	210,264	SF		
4	1-inch overlay (S-4.75A Asphalt)	16,862	SF		
5	Milling of Street Pavement Transitions and Asphalt Patching associated with Drainage and Waterline Improvements	16,033	SF		
6	Roadway Pavement Markings (24" wide Stop Bar-thermoplastic)	280	LF		
7	Roadway Pavement Markings (Ground Painted "STOP" lettering)	28	EA.		
8	Roadway Pavement Markings (8" wide painted solid white crosswalk line)	635	LF		
9	Site Restoration	1	LS		
10	Open Cut & Patch Asphalt Road (exclude 9.5B surface overlay Asphalt) associated with drainage and waterline improvements	6,742	SF		
<b>Subtotal Price</b>					

<b>Waterline Improvements Base Bid</b>					
<b>Item No.</b>	<b>Description</b>	<b>Est. Quantity</b>	<b>Unit</b>	<b>Unit Price</b>	<b>Total Price</b>
1	Clearing and Grubbing	1	LS		
2	Erosion Control Implementation & Removal	1	LS		
3	Ex. Concrete/Asphalt driveway removal, disposal & replacement with 4" thick concrete	29	EA		
4	6-inch PVC (C900) water line	2,111	LF		
6	6-inch DIP at street crossings	271	LF		
5	6-inch tapping sleeve and valve assembly	4	EA		
6	6-inch, 45° Bend	6	EA		
7	6-inch gate valve	6	EA		
8	6-inch tee	4	EA		
9	6-inch cross	1	EA		
10	Fire Hydrant Assembly	2	EA		
11	Fire Hydrant Relocation/Removal	2	EA		
12	Water service connections	54	EA		
13	New water connection with meter boxes and 1" meter setter	3	EA		
14	Connection to Existing water main	6	EA		
15	Abandonment/plugging of existing water main	1	LS		
16	Site Restoration	1	LS		
<b>Subtotal Price</b>					

<b>Drainage Improvement Base Bid</b>					
<b>Item No.</b>	<b>Description</b>	<b>Est. Quantity</b>	<b>Unit</b>	<b>Unit Price</b>	<b>Total Price</b>
1	General clearing within the limits of disturbance	1	LS		
2	Erosion Control Implementation & Removal	1	LS		
3	1' +/- deep swale with 4:1 side slopes	180	LF		
4	Select Fill, (furnished, placed, and compacted)	1	LS		
7	36" x 24" Drop inlet (840.14) with frame & grate (840.16) – installed	18	EA		
8	42" x 42" Junction Box (STMH) (840.31) with frame & grate (840.16) – installed	1	EA		
9	Remove existing pipe, furnish & install 30" dia. HP Storm Pipe	430	EA		
10	Remove existing pipe, furnish & install 24" dia. HP Storm Pipe	113	EA		
11	Remove existing pipe, furnish & install 18" dia. HP Storm Pipe	249	EA		
12	Furnish & install 15" dia. HP Storm Pipe	68	LF		
13	Flared End Section for 30" HP storm pipe	2	EA		
14	Flared End Section for 24" HP storm pipe	1	EA		
15	30" x 24" Reducer connected to existing	2	EA		
16	Existing Waterline Lowering	6	EA		
<b>Subtotal Price</b>					

**Total of Lump Sum (Base Bid) = Total Base Bid Price**      \$ \_\_\_\_\_

\_\_\_\_\_

<b>E. Gallery Row Street Resurfacing and Drainage improvements Add Alternate #1</b>					
<b>Item No.</b>	<b>Description</b>	<b>Est. Quantity</b>	<b>Unit</b>	<b>Unit Price</b>	<b>Total Price</b>
1	<b>E. Gallery Row from S. Wrightsville Ave. to S. Virginia Dare Trail Resurfacing:</b> 1.75-inch surface overlay	13,962	SF		
2	<b>E. Gallery Row Drainage Improvements:</b> 468 LF of 30" HPPP, 33 LF of 18" HPPP, 44 LF of 22"X36" corrugated aluminum arch pipe, 1 junction box with frame and cover and 4 pipe connections. Approximately 400 SF permanent pavement repair.	1	LS		
<b>Subtotal Price</b>					
<b>Total – E. Gallery Row Street Resurfacing and Drainage Improvements Add Alternate 1</b>					

<b>Drainage Add Alternate #2</b>					
<b>Item No.</b>	<b>Description</b>	<b>Est. Quantity</b>	<b>Unit</b>	<b>Unit Price</b>	<b>Total Price</b>
1	<b>S. Memorial Ave. South of Bonnett St.:</b> 130 LF of 24" HPPP.	130	LF		
<b>Subtotal Price</b>					
<b>Total – Drainage Add Alternate #2</b>					

5.04 Bidder agrees that the Work will be substantially complete and will be completed and ready for final payment in accordance with Paragraph 15.06 of the General Conditions and the Supplementary Conditions on or before the dates or within the number of calendar days indicated in the Agreement.

**ARTICLE 6 – ATTACHMENTS TO THIS BID**

6.01 The following documents are submitted with and made a condition of this Bid:

- A. List of Proposed Subcontractors;
- B. List of Proposed Suppliers;
- C. List of Project References;
- D. Evidence of authority to do business in the state of the Project; or a written covenant to obtain such license within the time for acceptance of Bids;

- E. Contractor's License No.: \_\_\_\_\_ [or] Evidence of Bidder's ability to obtain a State Contractor's License and a covenant by Bidder to obtain said license within the time for acceptance of Bids;

**ARTICLE 7 – DEFINED TERMS**

- 7.01 The terms used in this Bid with initial capital letters have the meanings stated in the Instructions to Bidders, the General Conditions, and the Supplementary Conditions.

**ARTICLE 8 – BID SUBMITTAL**

BIDDER: *[Indicate correct name of bidding entity]*

\_\_\_\_\_  
By:  
*[Signature]* \_\_\_\_\_

*[Printed name]* \_\_\_\_\_  
*(If Bidder is a corporation, a limited liability company, a partnership, or a joint venture, attach evidence of authority to sign.)*

Attest:  
*[Signature]* \_\_\_\_\_

*[Printed name]* \_\_\_\_\_

Title: \_\_\_\_\_

Submittal Date: \_\_\_\_\_

Address for giving notices:  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Telephone Number: \_\_\_\_\_

Fax Number: \_\_\_\_\_

Contact Name and e-mail address: \_\_\_\_\_  
\_\_\_\_\_

Bidder's License No.: \_\_\_\_\_  
*(where applicable)*